



KEY:

- Ⓐ Rear headrest straps
- Ⓑ Seatbelt/Baby Seat openings
- Ⓒ Front headrest straps
- Ⓓ Seat cover zipper
- Ⓔ Removable headrest straps
- Ⓕ Elastic bungee
- Ⓖ Seat d-ring

ATTACHING THE HAMMOCK: For Vehicles With Detachable Headrests

Remove the front and rear headrests. Place the headrest columns through the D-rings at the end of each strap. There are three grommet holes associated with each headrest. To avoid bunching of the Hammock, move the straps right or left between the grommet holes so they are in the best position for your vehicle. Repeat for each headrest. Tighten all straps so the bottom of the hammock still touches the seat and there is no slack in the foot well between the front and rear seats. Carry bag can attach to the hammock by looping the headrest straps (A) through the 3 small d-rings located on the back of the bag. To help the hammock stay correctly positioned on the seats, tie one of the elastic bungee (F) located on the bottom of the hammock to each of the seat d-rings (G) and slide under the edge of the seat.

ATTACHING THE HAMMOCK: For Vehicles Without Detachable Headrests

There are three grommet holes available with each headrest. To avoid bunching of the Hammock, move the straps right or left between the grommet holes so they are in the best position for your vehicle. Connect the removable headrest straps (E) and place around the front and rear headrests. Tighten all straps so the bottom of the hammock still touches the seat. Carry bag can attach to the hammock by looping the headrest straps (A) through the 3 small d-rings located on the back of the bag. To help the hammock stay correctly positioned on the seats, tie one of the elastic bungee (F) located on the bottom of the hammock to each of the seat d-rings (G) and slide under the edge of the seat.

ATTACHING THE SEAT COVER:

The Wander Hammock can also be used as a seat cover for all or just some of the seat. To use for the whole seat, start by following the applicable directions above. However, do not connect the straps to the front headrests. Instead pull the front part of the seat cover down toward the floor of the vehicle.

If you wish to split the seat cover as a hammock, just connect one of the straps to the headrest on that side of the vehicle per the instructions above and then unzip the hammock using the seat cover zipper (D).

WASHING INSTRUCTIONS:



1. Brush off loose dirt with a dry brush
2. As needed, wipe off with a damp sponge and mild soap
3. If necessary, rinse in a tub without soap
4. Machine wash in front-loading unit (DO NOT use machine with agitator; agitator could cause damage not covered under warranty) with cold water and mild soap (Ivory Flakes, Woolite, Sport Wash, Etc.) No detergents
5. Rinse thoroughly to eliminate soap residue.
6. Hang to dry

English 01/09

For additional information:

877.847.3868

:: www.kurgo.com

:: info@kurgo.com

kurgo